



3/8-16 thread x 0.75" min deep
 (4) Holes equispaced on $\text{Ø} 5.875''$ B.C.

- Notes:-**
1. With a positive current applied to green leads (x3) with respect to orange leads (x3), rotation shall be clockwise facing mounting end of motor.
 With this rotation a positive voltage shall be generated on black lead of of tach with respect to white lead.
 2. Motor can be mounted in any position
 3. Thermostat set to open at $90^\circ\text{C} \pm 6^\circ\text{C}$ & close at $70^\circ \pm 6^\circ\text{C}$ falling.
 N.C. contacts rated to 3.0 Amps, 250V. AC., (2) Yellow leads
 4. All dimensions in inches with mm in ().

Model	Length "L" Max
TT-4203	11.68" (297)
TT-4204	12.68" (322)
TT-4205	13.68" (347)
TT-4206	14.68" (373)
TT-4207	15.68" (398)
TT-4208	16.68" (424)
TT-4209	17.68" (449)

				Tolerances. X.XX = ± 0.015 X.XXX = ± 0.005 Ang. Dim. = $\pm 1^\circ$		Scale : NTS		Weight :
				Date 25/11/05		Material : SEE NOTES Remove all burrs and sharp corners		
				Name POB		Motor Outline TT 420X-1010		
Issue	ECO. No.	Date	Name	App'd	Norm	Callan Technology Ltd.		
						TT 420X-1010		
						Sheet 1 of 1		