



3/8-16 thread x 0.75" min deep
 (4) Holes equispaced on Ø 5.875" B.C.

(3) Holes - #8-32
 equispaced as shown
 on 3.687" B.C.
 (EndCover Mounting Holes)

Model	Length "L" Max
TT-4203	11.68" (297)
TT-4204	12.68" (322)
TT-4205	13.68" (347)
TT-4206	14.68" (373)
TT-4207	15.68" (398)
TT-4208	16.68" (424)
TT-4209	17.68" (449)

- Notes:-**
- With a positive current applied to pin C with respect to pin D, rotation shall be clockwise facing mounting end of motor. With this rotation a positive voltage shall be generated on pin J of tach with respect to pin K.
 - Motor can be mounted in any position
 - Thermostat set to open at 90°C ± 6°C & close at 70° ± 6°C falling. N.C. contacts rated to 3.0 Amps, 250V. AC., pins A & F
 - All dimensions in inches with mm in ().

				Tolerances. X.XX = ± 0.015 X.XXX = ± 0.005 Ang. Dim. = ± 1°		Scale : NTS		Weight :
				Date 25/11/05		Material : SEE NOTES Remove all burrs and sharp corners		
				Name POB		Motor Outline TT 420X-1011		
Issue	ECO. No.	Date	Name	App'd	Norm	TT 420X-1011		
Callan Technology Ltd.						TT 420X-1011		
						Sheet 1 of 1		